

Package: remedy (via r-universe)

January 20, 2025

Title 'RStudio' Addins to Simplify 'Markdown' Writing

Version 0.1.1

Description An 'RStudio' addin providing shortcuts for writing in 'Markdown'. This package provides a series of functions that allow the user to be more efficient when using 'Markdown'. For example, you can select a word, and put it in bold or in italics, or change the alignment of elements inside your Rmd. The idea is to map all the functionalities from 'remedy' on keyboard shortcuts, so that it provides an interface close to what you can find in any other text editor.

License MIT + file LICENSE

URL <https://github.com/ThinkR-open/remedy>

BugReports <https://github.com/ThinkR-open/remedy/issues>

Imports knitr, rstudioapi, rematch2, utils, stats

Suggests testthat, rmarkdown

Encoding UTF-8

Language en-US

LazyData true

RoxygenNote 7.1.0

VignetteBuilder knitr

Repository <https://thinkr-open.r-universe.dev>

RemoteUrl <https://github.com/ThinkR-open/remedy>

RemoteRef HEAD

RemoteSha eb8fbdd606d9b106c1aed6b5d30908b8c8ae7e4f

Contents

align_arrow	2
align_equal	3
backtickr	3

blockquoter	4
chunknamer	4
chunkr	5
chunksplitr	6
footnoter	6
h1r	7
htmlcommentr	7
id_ref	8
imager	9
is_link	9
italicsr	10
latexpr	11
listr	11
remedy_example	12
remedy_opts	13
rightr	13
tabler	14
urlr	15
xaringanr	15
youtuber	16

Index**17**

<i>align_arrow</i>	<i>Align a highlighted region's assignment operators.</i>
--------------------	---

Description

Align a highlighted region's assignment operators.

Usage

```
align_arrow()
```

Value

Aligns the single assignment operators (<-) within a highlighted region.

Examples

```
## Not run:
remedy_example(
  c( "# Align arrows",
    "a <- 12",
    "aaa <- 13"),
  align_arrow
)

## End(Not run)
```

align_equal*Align a highlighted region's assignment operators.*

Description

Align a highlighted region's assignment operators.

Usage

```
align_equal()
```

Value

Aligns the equal sign assignment operators (=) within a highlighted region.

Examples

```
## Not run:  
remedy_example(  
  c( "# Align equal signs",  
    "a = 12",  
    "aaa = 13"),  
  align_equal  
)  
  
## End(Not run)
```

backtickr*Backtick*

Description

Backtick selected word(s)

Usage

```
backtickr()
```

Value

a backticked text selection

Examples

```
## Not run:
remedy_example(
  c( "to_backtick"),
  backtickr
)

## End(Not run)
```

blockquoter

Convert to blockquote

Description

Turn the selected text into a blockquote.

Usage

```
blockquoter()
```

Value

a markdown blockquote

Examples

```
## Not run:
remedy_example(
  c( "to_blockquote"),
  blockquoter
)

## End(Not run)
```

chunknamer

Interactively Add Names to Chunks

Description

Addin that add in bulk a names to unnamed chunks in a Rmarkdown document in the source editor.

Usage

```
chunknamer()
```

Details

By default the addin will use "remedy" as the stem of the chunk names. this can be changed using `remedy_opts$set(name='ANOTHER NAME')`. The names are then added in sequential order using an

chunkr

Interactively Create Rmarkdown Chunks

Description

Addin that splits full documents into Rmarkdown chunks or wraps highlighted text in an active RStudio document editor in a Rmarkdown chunk.

Usage

```
chunkr()  
chunkr_doc()  
chunkr_section()
```

Details

Setting `remedy_opts$set(list(full_doc=TRUE))` chunkr will convert entire document by `remedy_opts$get('token_purl')`. The default token is the output from a `purl` conversion (## —chunk name,chunk options—).

Setting `remedy_opts$set(list(full_doc=FALSE))`, user highlights text and chunkr will wrap a new Rmarkdown chunk around it, utilizing the other options in `remedy_opts`.

Examples

```
## Not run:  
remedy_example(  
  c( "# Create a chunk",  
    "a <- 12",  
    "aaa <- 13"),  
  chunkr  
)  
  
## End(Not run)
```

`chunksplitr`*Split Chunk*

Description

Split a chunk into two chunks

Usage

```
chunksplitr()
```

Details

Will split below row of the current cursor position or under the highlighted text.

`footnoter`*Footnote*

Description

Create a footnote from selected text.

Usage

```
footnoter()
```

Value

footnote text (in markdown)

Examples

```
## Not run:  
remedy_example(  
  c( "# Create a footnote"),  
  footnoter  
)  
  
## End(Not run)
```

h1r

Convert to header

Description

Convert selected text into a header.

Usage

```
h1r()  
h2r()  
h3r()  
h4r()  
h5r()  
h6r()
```

Value

a markdown header

Examples

```
## Not run:  
remedy_example( c( "h1"), h1r)  
remedy_example( c( "h2"), h2r)  
remedy_example( c( "h3"), h3r)  
remedy_example( c( "h4"), h4r)  
remedy_example( c( "h5"), h5r)  
remedy_example( c( "h6"), h6r)  
  
## End(Not run)
```

htmlcommentr

html commenting

Description

RStudio addin to add/remove html comments to highlighted text

Usage

```
htmlcommentr()
```

Details

Highlighting text will add html comment tags around it

Highlighting commented text will remove tags.

Highlighting

Something COMMENT Something

Something <!-- COMMENT --> Something

New Comment

Something COMMENT [cursor here] Something

Something COMMENT <!-- --> Something

Start of Row

[cursor here] Something COMMENT Something

<!-- Something COMMENT Something -->

Highlighting Multiple rows

Something COMMENT Something

Something COMMENT Something

<!-- Something COMMENT Something -->

Something COMMENT Something -->

Examples

```
## Not run:
remedy_example( c( "<b>This is bold</b>" ), htmlcommentr)

## End(Not run)
```

id_ref

urlr

Description

Convert selected text into a markdown ref.

Usage

`id_ref()`

Value

A referenced content

Note

Only the three most common reference types are implemented: id, fig, and tab.

Examples

```
## Not run:  
remedy_example(  
  "pouet",  
  id_ref  
)  
  
## End(Not run)
```

*imager**Imager*

Description

Convert the selected path into an embedded image

Usage

```
imager()
```

Value

a markdown image link

Examples

```
## Not run:  
remedy_example(  
  c( "https://thinkr.fr/wp-content/uploads/2015/03/thinkR1.png"),  
  imager  
)  
  
## End(Not run)
```

*is_link**Check if text is a relative link or URL*

Description

Check if text is a relative link or URL

Usage

```
is_link(text)
```

Arguments

text	A character string
------	--------------------

Value

TRUE or FALSE

Examples

```
is_link("www.google.com")
is_link("figs/plot.png")
```

italicsr

Emphasize

Description

Emphasize the selected text.

Usage

```
italicsr()
boldr()
strikerr()
```

Value

emboldened, italicized or strikethrough text (in markdown)

Examples

```
## Not run:
remedy_example(
  c( "to_italic"),
  italicsr
)
remedy_example(
  c( "to_bold"),
  boldr
)
remedy_example(
  c( "to_strike"),
  striker
)

## End(Not run)
```

`latexpr`*LaTeX*

Description

Convert the selected text in inline LaTeX.

Usage`latexpr()`**Value**

inline LaTeX text (in markdown)

Examples

```
## Not run:  
remedy_example(  
  c( "Latex stuffs"),  
  latexpr  
)  
  
## End(Not run)
```

`listr`*Convert to list*

Description

Convert selected text into an (un)ordered list.

Usage`listr()``olistr()`**Value**

`listr()` returns an unordered markdown list

`olistr()` returns an ordered markdown list

Examples

```
## Not run:
#unordered list
remedy_example(c('line 1','line 2'),listr)

#ordered list
remedy_example(c('line 1','line 2'),olistr)

## End(Not run)
```

remedy_example

Functions to run examples and tests

Description

Utility functions to deploy functions and tests for addins

Usage

```
remedy_example(txt, addin, mark = entire_document)

scratch_file()

entire_document()

individual_lines()

set_text(txt = "", sec, mark)
```

Arguments

txt	character, text to place in temporary document
addin	function, addin function to deploy
mark	function, highlight using entire_document or individual_lines
sec	source editor context object

Details

These function only will work in a RStudio IDE

Value

New document in source editor of RStudio

`remedy_opts`*Default and current remedy options*

Description

Options for functions in the `remedy` package. When running R code, the object `remedy_opts` (default options) is not modified by chunk headers (local chunk options are merged with default options), whereas `remedy_opts_current` (current options) changes with different chunk headers and it always reflects the options for the current chunk.

Normally we set up the global options once in the first code chunk in a document using `remedy_opts$set()`, so that all *latter* chunks will use these options. Note the global options set in one chunk will not affect the options in this chunk itself, and that is why we often need to set global options in a separate chunk.

Below is a list of default chunk options, retrieved via `remedy_opts$get()`:

Usage

```
remedy_opts
```

```
remedy_opts_current
```

Format

An object of class `list` of length 5.

An object of class `list` of length 5.

Note

`remedy_opts_current` is read-only in the sense that it does nothing if you call `remedy_opts_current$set()`; you can only query the options via `remedy_opts_current$get()`.

Examples

```
remedy_opts$get()
```

`rightr`*Mover*

Description

Copy a selected text or the current line to the right

Usage

```
rightr()
```

Value

a clone of the line

Examples

```
## Not run:  
remedy_example(  
  c( "I like to move it "),  
  rightr  
)  
  
## End(Not run)
```

tabler

Tabler

Description

Insert a table in your file.

Usage

```
tabler()
```

Value

a markdown table

Examples

```
## Not run:  
remedy_example(  
  "head(iris)",  
  tabler  
)  
  
## End(Not run)
```

<code>urlr</code>	<i>urlr</i>
-------------------	-------------

Description

Convert selected text into a link

Usage

```
urlr()
```

Value

a markdown link

Examples

```
## Not run:  
remedy_example(  
  "https://www.thinkr.fr",  
  urlr  
)  
  
## End(Not run)
```

<code>xaringanr</code>	<i>xaringan</i>
------------------------	-----------------

Description

xaringan pull left and pull right

Usage

```
xaringanr()
```

Value

a template for xaringan pull left and right

Examples

```
## Not run:
remedy_example(
  '',
  xaringanr
)

## End(Not run)
```

youtuber

Addin to create markdown youtube links

Description

Highlight youtube link in source editor and it will be converted to a markdown link with an image saved in youtube.

Usage

```
youtuber()
```

Details

if remedy_opts\$get('youtube_output')=='md' then the output will be of the form
 [![Alternative text](Youtube Image)](Link to Video). (useful for github readme)
 if remedy_opts\$get('youtube_output')=='html' then the output will be of the form
<iframe width="remedy_opts\$get('youtube_width')" height="remedy_opts\$get('youtube_height')"
src="link to video" frameborder="0" allowfullscreen></iframe>
Default Settings:
remedy_opts\$get('youtube_output'): str(remedy::remedy_opts\$get('youtube_output'))
remedy_opts\$get('youtube_height'): str(remedy::remedy_opts\$get('youtube_height'))
remedy_opts\$get('youtube_width'): str(remedy::remedy_opts\$get('youtube_width'))

Examples

```
## Not run:
remedy_example(
  "https://www.youtube.com/watch?v=dQw4w9WgXcQ",
  youtuber
)

## End(Not run)
```

Index

* **datasets**
 remedy_opts, 13

align_arrow, 2
align_equal, 3

backtickr, 3
blockquoter, 4
boldr (italicsr), 10

chunknamer, 4
chunkr, 5
chunkr_doc (chunkr), 5
chunkr_section (chunkr), 5
chunksplitr, 6

entire_document (remedy_example), 12

footnoter, 6

h1r, 7
h2r (h1r), 7
h3r (h1r), 7
h4r (h1r), 7
h5r (h1r), 7
h6r (h1r), 7
htmlcommentr, 7

id_ref, 8
imager, 9
individual_lines (remedy_example), 12
is_link, 9
italicsr, 10

latexpr, 11
listr, 11

olistr (listr), 11

purl, 5

remedy_example, 12

 remedy_opts, 5, 13
 remedy_opts_current (remedy_opts), 13
 rightr, 13

 scratch_file (remedy_example), 12
 set_text (remedy_example), 12
 striker (italicsr), 10

 tabler, 14

 urlr, 15

 xaringanr, 15

 youtuber, 16