

Package: testdown (via r-universe)

June 4, 2024

Title 'testthat' Results to Bookdown

Version 0.1.2.9000

Description Turn your 'testthat' results a Bookdown.

License MIT + file LICENSE

URL <https://github.com/thinkr-open/testdown>

BugReports <https://github.com/thinkr-open/testdown/issues>

Imports attempt, cli, devtools, fs, here, htmltools, knitr, magrittr, purrr, R6, rmarkdown, roxygen2, stats, testthat, tools, utils

Suggests bookdown, rlang, usethis, withr, yaml

Encoding UTF-8

LazyData true

RoxygenNote 7.2.3

Repository <https://thinkr-open.r-universe.dev>

RemoteUrl <https://github.com/ThinkR-open/testdown>

RemoteRef HEAD

RemoteSha 35e437c1cec234ab0fee8102a72f2cca47067475

Contents

test_down	2
test_down_example	2

Index	4
--------------	----------

test_down	<i>testthat to bookdown</i>
-----------	-----------------------------

Description

This function turns the results of `testthat` into a bookdown. Each chapter is a context. The first page gives a summary of all the tests.

Usage

```
test_down(
  project_name = NULL,
  author = NULL,
  pkg = here::here(),
  environment = here::here(),
  book_path = "tests/testdown",
  with_help = TRUE,
  open = interactive()
)
```

Arguments

<code>project_name</code>	The name you want to give to the project. The default is 'NULL', which will be then be converted to <code>basename(here::here())</code> .
<code>author</code>	The author of the test report. Default is set to 'NULL', then it will be skipped.
<code>pkg</code>	The path to the package to document. Default is <code>here::here()</code> .
<code>environment</code>	A name for the testing environment. Default is <code>here::here()</code> .
<code>book_path</code>	The path to the bookdown output. Default is <code>"tests/testdown"</code> .
<code>with_help</code>	Should the help appendix be added? Default is 'TRUE'.
<code>open</code>	Should the bookdown be opened once compiled? Default is <code>interactive()</code> .

test_down_example	<i>Run a test_down example</i>
-------------------	--------------------------------

Description

Run a `test_down` example

Usage

```
test_down_example(  
  project_name = NULL,  
  author = NULL,  
  environment = here::here(),  
  pkg = system.file("fakepkg", package = "testdown"),  
  book_path = "tests/testdown",  
  with_help = TRUE,  
  open = interactive()  
)
```

Arguments

project_name	The name you want to give to the project. The default is 'NULL', which will be then be converted to 'basename(here::here())'.
author	The author of the test report. Default is set to 'NULL', then it will be skipped.
environment	A name for the testing environment. Default is 'here::here()'.
pkg	The path to the package to document. Default is 'here::here()'.
book_path	The path to the bookdown output. Default is "tests/testdown".
with_help	Should the help appendix be added? Default is 'TRUE'.
open	Should the bookdown be opened once compiled? Default is 'interactive()'.

Value

Path to the report

Examples

```
if (interactive()){  
  dir_book <- tempfile()  
  dir.create(dir_book)  
  test_down_example(book_path = dir_book)  
}
```

Index

test_down, [2](#)

test_down_example, [2](#)